

Features

- ◆ A Variety of Pressure/Vacuum Settings – 3" water column, 1 oz., 8 oz., 12 oz. pressure settings and 8" water column or 1/2 oz. vacuum settings are factory preset and tested.
- ◆ Reliable Service – self-guided poppet assembly ensures consistent seating of the pressure/vacuum valve.
- ◆ Corrosion-Resistant Construction – Duratuff® composite body assures a long service life.
- ◆ Easy Installation – 523V is available in 2" and 3" threaded versions or slip-on models that provide for attachment to the vent line with allen head screws and radial sealing O-ring.



- ◆ Complies with NFPA 30 Requirements – for venting gasoline vapors upward.
- ◆ High Maximum Flow Rate – 7000 SCFH at 2 psi pressure drop.
- ◆ 40-Mesh Stainless Steel Wire Screen – helps prevent debris and insects from entering the tank vent lines.

Ordering Specifications

Product #	Description	Identification		
		Label Color	lb.	kg
523V-1100	2" 8 oz pres., 1/2 oz. Vac. Thread-On	Red	1.65	.75
523V-1150	2" 8 oz pres., 1/2 oz. Vac. Slip-On	Red	1.65	.75
523V-3100	3" 8 oz pres., 1/2 oz. Vac. Thread-On	Red	3.2	1.45
523V-3150	3" 8 oz pres., 1/2 oz. Vac. Slip-On	Red	3.2	1.45
523V-2200	2" 1 oz pres., 1/2 oz. Vac. Thread-On	Silver	1.65	.75
523V-2250	2" 1 oz pres., 1/2 oz. Vac. Slip-On	Silver	1.65	.75
523V-3200	3" 1 oz pres., 1/2 oz. Vac. Thread-On	Silver	3.2	1.45
523V-2203	2" 3" WC pres., 8" WC Vac. Thread-On	Yellow	1.65	.75
523V-2253	2" 3" WC pres., 8" WC Vac. Slip-On	Yellow	1.65	.75
523V-3203	3" 3" WC pres., 8" WC Vac. Thread-On	Yellow	3.2	1.45
523V-3253	3" 3" WC pres., 8" WC Vac. Slip-On	Yellow	3.2	1.45

Materials

Body: Aluminum
O-ring: Nitrile



523SA
(Bottom View)

523SA
(Top View)

Ordering Specifications

Product #	Description	in.	mm	lb.	kg
523A-1003	3" Thread-On Adaptor for use with 523V Pressure / Vacuum Vents	2 x 3	51 x 76	.47	.213
523SA-1003	3" Slip-On Adaptor for use with 523V Pressure / Vacuum Vents	2 x 3	51 x 76	.63	.286
523SA-1002	2" Slip-On Adaptor for use with 523V Pressure / Vacuum Vents	2 x 2	51 x 51	.31	.141

523V Instruction Sheet Order Number: **H11972M**

OPW 523V Pressure Vacuum Vent

Pressure Vacuum Vents are installed on the top of vent pipes from underground or above ground fuel storage tanks. The vent cap and internal wire screen are designed to protect the tank vent lines against intrusion and blockage from water, debris or insects. A normally closed poppet in the valve opens at a predetermined pressure or vacuum setting to allow the tank to vent.

Conversion Table

Measurement Units	=	Oz.	PSI	In H ₂ O (WC)	In Hg (Merc)	Bar
Bar	x	236.0	14.5	401.4	29.53	
In. Hg (Mercury)	x	7.843	0.49	13.6		0.034
In H ₂ O (WC)	x	0.578	0.04		0.074	0.002
PSI	x	16.00		27.68	2.04	0.069
Oz.	x		0.063	1.73	0.128	0.004

Replacement Parts

Part Number	Description
H11432M	O-ring for 2" Thread
H11456M	O-ring for 3" Thread

OPW 523V Series Adaptor Bushings

The 523V Series Adaptor Bushings are designed to thread into the base of 2" threaded 523V vents. The adaptor bushings convert a 2" 523V to 3" threaded, 2" slip-on or 3" slip-on connection.